## **UV Aging Testing Chamber**

-----the internal dimension can be customized

## **Application:**

UV Aging Testing Machine is to simulate the sun lighting, and it's specialized in the simulation of products in outdoors for a long time. The ultraviolet radiation in the sun is destructive on its exposure, only a few days or weeks, the equipment can reproduce the destruction outdoors for months or years.

## Parameter:

Internal Dimension	W1150×H500×D500 mm
External Dimension	W1400×H1600×D750 mm
Temperature Range	(RT+15°C) $\sim$ 70°C (adjustable& controlled)
Humidity Range	≥90%R.H (only display, can not control)
Temp.Fluctuation	≤±0.5°C
Humidity Uniformity	≤±3%
Black Panel Temp.	40°C∼65°C
Distance between tubes	100~500mm±30mm
Distance between specimen	50±2mm
and tubes	
Tubes power	40W, 10 pieces in total, Length:1200mm
UV wave length	$280$ nm $\sim$ 420nm (fixed, can not adjustable)
Irradiation Range	$\leq 1$ w/m2 (adjustable, 0.4~1.4w/m2)
AI SI Li (CHINA) TEST EQUIPMENT CO., LTD	

Tel.:0086-769-23164266Fax:0086-769-22851784E-mail: sales8@aslitesting.comCompany Add.:Building C,JinHui Industrial Park, LiXin town,East City district 523125,DongGuan City,China

## **Pictures**



Company Add.:Building C,JinHui Industrial Park, LiXin town,East City district 523125,DongGuan City,China